

221213

Weatherproofing Kit for Connectors and Splices, includes butyl rubber and PVC tape



CHARACTERISTICS

Dimensions

| | |
|--------------|---|
| Nominal Size | 1-1/4 in 1-5/8 in 1/2 in 1/4 in 2-1/4 in 3/8 in 5/8 in 7/8 in |
|--------------|---|

General Specifications

| | |
|----------------------|--|
| Application | Provides additional moisture seal for cable connections |
| Applications per Kit | Four 1/2 in-7/8 in Twelve 1/2 in-1/2 in Twelve 1/2 in-7/8 in to device Two 1/2 in-2-1/4 in |
| Includes | One roll of 2 in PVC tape Six rolls of 2-1/2 in butyl rubber tape Two rolls of 3/4 in PVC tape |
| Material Type | Butyl rubber tape PVC tape |
| Package Quantity | 1 |

Mechanical Specifications

| | |
|--|---|
| UV Resistance Test Method | Butyl test method in QUV weatherometer cycle of 8 hours UV at 150 °F then 4 hours of condensation at 104 °F PVC tape test method UL 510, ASTM D1000 |
| UV Resistance, minimum with no degradation | ≥1000 hours |
| Weather Resistance Test Method | 04AS00-03.6.0 MIL-STD-1344A, Method 1002 |

Packed Dimensions

| | |
|-----------------|-------------------|
| Height | 19.6 cm 7.7 in |
| Length | 9.6 cm 3.8 in |
| Shipping Weight | 1.52 kg 3.35 lb |
| Width | 17.4 cm 6.9 in |

Regulatory Compliance/Certifications

| | |
|----------------------------|--|
| Agency | Classification |
| RoHS 2002/95/EC | Compliant |
| China RoHS SJ/T 11364-2006 | Below Maximum Concentration Value (MCV) |
| ISO 9001:2008 | Designed, manufactured and/or distributed under this quality management system |

Product Specifications

221213

COMMSCOPE®



INCLUDED PRODUCTS



42615-10

Butyl Rubber Tape, 24 in



9905-41

Black 3/4 in PVC Tape, 66 ft



9905-71

Black 2 in PVC Tape, 20 ft
